



Lonking 龙工

CDM6125W WHEEL EXCAVATOR

Efficiency Rules the Future

TECHNICAL PARAMETERS

Name		Data
Basic	Operating weight	10000 kg
	Boom length	4000 mm
	Arm length	2000 mm
	Standard bucket	0.4 m ³
	Max.Travel speed	30 km/h
	Max.Swing speed	11 rpm
	Grade ability	30°(58%)
	Tire type	8.25-20
	Max.Traction force	60 kN
Engine	Engine model	YC4DK100
	Rated power	73.5 kW/2200 rpm
	Displacement	3.621 L
	Fqt fuel quantity	≥6 L/h
	Fuel tank	150 L
Hydraulic	Max.Flow(total)	150 L/min
	Max.Working pressure	28 MPa
	Max.Digging force	60 kN
	Hrdraulic oil tank	150 L
Working Range	A1 Max.Digging reach	7350 mm
	B1 Max.Ground digging reach	7200 mm
	C1 Max.Digging height	6945 mm
	D1 Max.Dumping height	5330 mm
	E1 Max.Digging depth	4300 mm
	F1 Max. Vertical digging depth	3900 mm
	G1 Min. Working radius	2500 mm
Overall Dimension	Transport demission (A×B×C)	7050×2330×2980 mm
	D Counterweight ground clearance	1250 mm
	E Min. Ground clearance	440 mm
	F Tail swing radius	2100 mm
	G Axle base	2600 mm
	H Wheel base	1770 mm

CONFIGURATION

Name	Type
Engine	Stage 3 emission
Main valve	Multiple unit
Main pump	Piston type
Swing motor	Piston type
Gearbox	Full hydraulic
Travel motor	Piston type

OPTIONAL

Custom bucket
Hydraulic hammer
Quick coupler
Hydraulic clamp
Supporting leg

PRODUCT FEATURES

Strong & Powerful Engine. Water Cooled, Four Stroke, HPCR(BOSCH)
High Efficiency Dual Air and Fuel Filters
Parallel Radiator Cooling System
LUDV Power Balanced Hydraulic System
LCD Monitor and Advanced Electronic Monitoring System
Safe and Comfortable Cab, Ergonomic Design
Working device adopts low alloy and high strength structural steel.
Standard with rear dozer, rear view camera, air conditioner



The following blank can be used for notes or comments.

For more information on Lonking products,
Please contact our local agent:

OPERATING WEIGHT:	10000kg
ENGINE POWER:	73.5kW
BUCKET CAPACITY:	0.4m ³
TRAVEL SPEED:	30km/h