



TECHNICAL PARAMETERS

	Name	Data
Basic	Operating weight	7000 kg
	Boom length	3300 mm
	Arm length	1850 mm
	Standard bucket	0.2-0.3 m ³
	Max.Travel speed	25 km/h
	Max.Swing speed	11 rpm
	Grade ability	30°(58%)
	Tire type	7.50-16
	Max.Traction force	45 kN
Engine	Engine model	YC4DK75
	Rated power	55 kW/2200 rpm
	Displacement	3.621 L
	Fqt fuel quantity	≥4 L/h
	Fuel tank	110 L
Hydraulic	Max.Flow(total)	150 L/min
	Max.Working pressure	25 MPa
	Max.Digging force	45 kN
	Hrdraulic oil tank	110 L
	A1 Max.Digging reach	6400 mm
	B1 Max.Ground digging reach	6200 mm
Working Range	C1 Max.Digging height	6800 mm
	D1 Max.Dumping height	4900 mm
	E1 Max.Digging depth	3300 mm
	F1 Max. Vertical digging depth	2900 mm
	G1 Min. Working radius	2300 mm
Overall	Transport demission (A×B×C)	5800×2100×2900 mm
	D Counterweight ground clearance	1060 mm
Dimension	E Min. Ground clearance	250 mm
	F Tail swing radius	1980 mm
	G Axle base	2400 mm
	H Wheel base	1660/1580 mm

CONFIGURATION

Name	Туре
Engine	Stage 3 emission
Main valve	Multiple unit
Main pump	Piston Type
Swing motor	Piston Type
Gearbox	MT(5 speed)
Travel motor	Heavyduty

OPTIONAL

Custom bucket	
Hydraulic hammer	
Quick coupler	
Hydraulic clamp	
Magnetic chuck	
Supporting leg	
Rear view camera	

PRODUCT FEATURES

Strong & Powerful Engine. Water Cooled, Four Stroke, HPCR(BOSCH)	
High Efficiency Dual Air and Fuel Filters	
Parallel Radiator Cooling System	
High efficiency and energy saving hydraulic system	
LCD Monitor and Advanced Electronic Monitoring System	
Safe and Comfortable Cab, Ergonomic Design	
Working device adopts low alloy and high strength structural steel.	
Standard with rear dozer, air conditioner	

For more information on Lonking products, Please contact our local agent:

LONKING 72 I

CDM6075W WHEEL EXCAVATOR



OPERATING WEIGHT: 7000kg

■ ENGINE POWER: 55kW

■ BUCKET CAPACITY: 0.2-0.3m³

25km/h

TRAVEL SPEED:

The following blank can be used for notes or comments.