



Lonking 龙工

CDM6070W WHEEL EXCAVATOR

Efficiency Rules the Future

TECHNICAL PARAMETERS

	Name	Data
Basic	Operating weight	6000 kg
	Boom length	3300 mm
	Arm length	1850 mm
	Standard bucket	0.2-0.3 m ³
	Max.Travel speed	25 km/h
	Max.Swing speed	11 rpm
	Grade ability	30°(58%)
	Tire type	7.50-16
Engine	Max.Traction force	45 kN
	Engine model	4D35G
	Rated power	48 kW/2200 rpm
	Displacement	3.621 L
	Fqt fuel quantity	≥4 L/h
Hydraulic	Fuel tank	110 L
	Max.Flow(total)	110 L/min
	Max.Working pressure	20 MPa
	Max.Digging force	45 kN
Working Range	Hdraulic oil tank	110 L
	A1 Max.Digging reach	6100 mm
	B1 Max.Ground digging reach	5910 mm
	C1 Max.Digging height	6870 mm
	D1 Max.Dumping height	4860 mm
	E1 Max.Digging depth	3300 mm
	F1 Max. Vertical digging depth	2900 mm
	G1 Min. Working radius	2300 mm
Overall Dimension	Transport demission (A×B×C)	5800×2100×2850 mm
	D Counterweight ground clearance	1060 mm
	E Min. Ground clearance	250 mm
	F Tail swing radius	1775 mm
	G Axle base	2400 mm
	H Wheel base	1660/1580 mm

CONFIGURATION

Name	Type
Engine	Stage 2 emission
Main valve	Multiple unit
Main pump	Piston Type
Swing motor	Piston Type
Gearbox	MT(5 speed)
Travel motor	Heavyduty

OPTIONAL

Custom bucket
Hydraulic hammer
Quick coupler
Hydraulic clamp
Magnetic chuck
Supporting leg
Rear view camera

PRODUCT FEATURES

Strong & Powerful MDI Engine. Water Cooled, Four Stroke.
High Efficiency Dual Air and Fuel Filters
Parallel Radiator Cooling System
High efficiency and energy saving hydraulic system
LCD Monitor and Advanced Electronic Monitoring System
Safe and Comfortable Cab, Ergonomic Design
Working device adopts low alloy and high strength structural steel.
Standard with rear dozer, air conditioner



The following blank can be used for notes or comments.

For more information on Lonking products,
Please contact our local agent:

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd., and may not be used without written permission.

2022/03

Specifications and design are subject to change without prior notice.
Machines shown may not include optional accessories.

- OPERATING WEIGHT: 6000kg
- ENGINE POWER: 48kW
- BUCKET CAPACITY: 0.2-0.3m³
- TRAVEL SPEED: 25km/h